





SRFX

CIRCULAR BRUSHES

Medium to heavy brush applications: long life, aggressive, very resistant.




Art.	Dimensions	Hole	Wire	rpm max
SRF125/25	Ø 125 x 20 mm	16, 12,7 mm	0,3 mm	6000
SRF150/25	Ø 150 x 32 mm	25, 22, 20, 16, 12,7 mm	0,3 mm	6000
SRF175/25	Ø 175 x 32 mm	25, 22, 20, 16 mm	0,3 mm	6000
SRF200/25	Ø 200 x 32 mm	25, 22, 20, 16, 13 mm	0,3 mm	4500
SRF250/25	Ø 250 x 32 mm	25, 22, 20, 16 mm	0,3 mm	3000

SRFXI

CIRCULAR BRUSHES

Medium to heavy brush applications: long life, aggressive, very resistant.




Art.	Dimensions	Hole	Wire	rpm max
SRF125/25I	Ø 125 x 20 mm	16, 12,7 mm	0,3 mm	6000
SRF150/25I	Ø 150 x 32 mm	25, 22, 20, 16, 12,7 mm	0,3 mm	6000
SRF175/25I	Ø 175 x 32 mm	25, 22, 20, 16 mm	0,3 mm	6000
SRF200/25I	Ø 200 x 32 mm	25, 22, 20, 16 mm	0,3 mm	4500
SRF250/25I	Ø 250 x 32 mm	25, 22, 20, 16 mm	0,3 mm	3000

STFX

CUP BRUSHES

Suited for angle grinders. paint and primer removal, roughing, light rust removal.




Art.	Diameter ø	Thread	Wire	rpm max
STF060	60 mm	M14	0,3 mm	12500
STF080	80 mm	M14	0,3 mm	11000
STF100	100 mm	M14	0,3 mm	8500
STF120	120 mm	M14	0,3 mm	6500

STFXI

CUP BRUSHES

Suited for angle grinders. paint and primer removal, roughing, light rust removal.




Art.	Diameter ø	Thread	Wire	rpm max
STF060I	60 mm	M14	0,3 mm	12500
STF080I	80 mm	M14	0,3 mm	11000
STF100I	100 mm	M14	0,3 mm	8500
STF120I	120 mm	M14	0,3 mm	6500

SCFX

BEVEL BRUSHES

Suited for angle grinders.




Art.	Thread	Wire	rpm max	Diameter ø
SCF090	M14	0,3 mm	125000	90 mm
SCF120	M14	0,3 mm	125000	120 mm
SCF150	M14	0,3 mm	6500	150 mm

SCFXI

BEVEL BRUSHES


Suited for angle grinders.



Art.	Thread	Wire	rpm max	Diameter ø
SCF090I	M14	0,3 mm	125000	90 mm
SCF120I	M14	0,3 mm	125000	120 mm
SCF150I	M14	0,3 mm	6000	150 mm

SRRX
TWISTED KNOTS CIRCULAR BRUSHES



Suited to clean welds and to remove paint, rust, encrustations and burrs. high operating speed.



Art.	Diameter ø	Hole	Wire	rpm max
SRR100	100 mm	22 mm	0,5 mm	12500
SRR150	150 mm	22 mm	0,5 mm	9000
SRR200	200 mm	22 mm	0,5 mm	6000

SRRX-M14
TWISTED KNOTS CIRCULAR BRUSHES



Suited to clean welds and to remove paint, rust, encrustations and burrs. high operating speed.



Art.	Diameter ø	Thread	Wire	rpm max
SRR100/M14	100 mm	M14	0,5 mm	12500
SRR115/M14	115 mm	M14	0,5 mm	12500
SRR125/M14	125 mm	M14	0,5 mm	11000

STRX
TWISTED KNOTS CUP BRUSHES


Suited to remove carbon, rust, paint and other contaminations



Art.	Diameter ø	Thread	Wire	rpm max
STR065	65 mm	M14	0,5 mm	12500
STR075	75 mm	M14	0,5 mm	8500
STR080	80 mm	M14	0,5 mm	8500
STR100	100 mm	M14	0,5 mm	8500
STR120	120 mm	M14	0,5 mm	6500

STRXI
TWISTED KNOTS CUP BRUSHES


Suited to remove carbon, rust, paint and other contaminations



Art.	Diameter ø	Thread	Wire	rpm max
STR065I	65 mm	M 14	0,5 mm	12500
STR075I	75 mm	M 14	0,5 mm	8500
STR080I	80 mm	M 14	0,5 mm	8500
STR100I	100 mm	M 14	0,5 mm	8500
STR120I	120 mm	M 14	0,5 mm	6500

SCRX
TWISTED KNOTS BEVEL BRUSHES



Suited to remove carbon, rust, paint and other contaminations. Tapered brush shaped to reach angles.



Art.	Diameter ø	Thread	Wire	rpm max
SCR100	100 mm	M14	0,5 mm	12500
SCR120	120 mm	M14	0,5 mm	12500

SCRXI
TWISTED KNOTS BEVEL BRUSHES

Suited to remove carbon, rust, paint and other contaminations. Tapered brush shaped to reach angles.




Art.	Diameter ø	Thread	Wire	rpm max
SCR100I	100 mm	M14	0,5 mm	12500
SCR120I	120 mm	M14	0,5 mm	12500



SRGX

CIRCULAR BRUSHES WITH SHAFT

Cleaning of light rust, paint, primer.




Art.	Diameter ø	Thickness	Shank	Wire	rpm max
SRG030/05	30 mm	5 mm	6 mm	0,3 mm	4500
SRG040/05	40 mm	5 mm	6 mm	0,3 mm	4500
SRG050/06	50 mm	6 mm	6 mm	0,3 mm	4500
SRG060/06	60 mm	6 mm	6 mm	0,3 mm	4500
SRG070/08	70 mm	8 mm	6 mm	0,3 mm	4500
SRG080/08	80 mm	8 mm	6 mm	0,3 mm	4500
SRG100/10	100 mm	10 mm	6 mm	0,3 mm	4500
SRG100/15	100 mm	15 mm	6 mm	0,3 mm	4500

SRGXI

CIRCULAR BRUSHES WITH SHAFT

Cleaning of light rust, paint, primer.




Art.	Diameter ø	Thickness	Shank	Wire	rpm max
SRG030/05I	30 mm	5 mm	6 mm	0,3 mm	4500
SRG040/05I	40 mm	5 mm	6 mm	0,3 mm	4500
SRG050/06I	50 mm	6 mm	6 mm	0,3 mm	4500
SRG060/06I	60 mm	6 mm	6 mm	0,3 mm	4500
SRG070/08I	70 mm	8 mm	6 mm	0,3 mm	4500
SRG080/08I	80 mm	8 mm	6 mm	0,3 mm	4500
SRG100/10I	100 mm	10 mm	6 mm	0,3 mm	4500
SRG100/15I	100 mm	15 mm	6 mm	0,3 mm	4500

SNGX

NYLON BRUSHES ON SHAFT

More flexible and resistant to breaking than steel wire. On metals it removes oxide and paint residues, scratching less and avoiding rust, on wood it prepares the surface.




Art.	Diameter ø	Shank	Grit	Color	rpm max
SNG075/080R	75 mm	6 mm	80	Red	4500
SNG075/180B	75 mm	6 mm	180	Blue	4500
SNG100/080R	100 mm	6 mm	80	Red	4500
SNG100/180B	100 mm	6 mm	180	Blue	4500

SGR075

TWISTED KNOTS BRUSH WITH SHAFT

Cleaning, removal of rust and weld seams




Diameter ø	75 mm
Shank	6 mm
Wire	0,5 mm
rpm max	12000

SGR075I

TWISTED KNOTS BRUSH WITH SHAFT

Cleaning, removal of rust and weld seams




Diameter ø	75 mm
Shank	6 mm
Wire	0,5 mm
rpm max	12000

SCG090

BEVEL BRUSHES WITH SHAFT

For light and medium rust and varnish removal and deburring



Diameter ø	90 mm
Shank	6 mm
Wire	0,3 mm
rpm max	12500

SCG090I

BEVEL BRUSHES WITH SHAFT

For light and medium rust and varnish removal and deburring




Diameter ø	90 mm
Shank	6 mm
Wire	0,3 mm
rpm max	12500

STGX

CUP BRUSHES WITH SHAFT

Cup shape, to reach the bottoms and to work frontally




Art.	Diameter ø	Shank	Wire	rpm max
STG050	50 mm	6 mm	0,3 mm	6500
STG070	70 mm	6 mm	0,3 mm	4500

STGXI

CUP BRUSHES WITH SHAFT

Cup shape, to reach the bottoms and to work frontally




Art.	Diameter ø	Shank	Wire	rpm max
STG050I	50 mm	6 mm	0,3 mm	6500
STG070I	70 mm	6 mm	0,3 mm	4500

SFGX

END BRUSHES

Suited for hard-to-reach spots and frontal cleaning.




Art.	Diameter ø	Shank	Wire	rpm max
SFG010	10 mm	6 mm	0,3 mm	20000
SFG015	15 mm	6 mm	0,3 mm	20000
SFG020	20 mm	6 mm	0,3 mm	20000
SFG025	25 mm	6 mm	0,3 mm	20000
SFG030	30 mm	6 mm	0,3 mm	20000

SFGXI

END BRUSHES

Suited for hard-to-reach spots and frontal cleaning.




Art.	Diameter ø	Shank	Wire	rpm max
SFG010I	10 mm	6 mm	0,3 mm	20000
SFG015I	15 mm	6 mm	0,3 mm	20000
SFG020I	20 mm	6 mm	0,3 mm	20000
SFG025I	25 mm	6 mm	0,3 mm	20000
SFG030I	30 mm	6 mm	0,3 mm	20000

SFPX

TIP END BRUSHES

Suited for hard-to-reach spots and frontal cleaning.




Art.	Diameter ø	Shank	Wire	rpm max
SFP012	12 mm	6 mm	0,3 mm	20000
SFP024	24 mm	6 mm	0,3 mm	20000



SFPXI

TIP END BRUSHES

Suited for hard-to-reach spots and frontal cleaning.




Art.	Diameter ø	Shank	Wire	rpm max
SFP0121	12 mm	6 mm	0.3 mm	20000
SFP0241	24 mm	6 mm	0.3 mm	20000

SFRX

TWISTED KNOTS END BRUSHES

Suited for hard-to-reach spots and frontal cleaning.




Art.	Diameter ø	Shank	Wire	rpm max
SFR019	19 mm	6 mm	0,5 mm	20000
SFR022	22 mm	6 mm	0,5 mm	20000

SFRXI

TWISTED KNOTS END BRUSHES

Suited for hard-to-reach spots and frontal cleaning.



Art.	Diameter ø	Shank	Wire	rpm max
SFR019I	19 mm	6 mm	0,5 mm	20000
SFR022I	22 mm	6 mm	0,5 mm	20000

0331

WIRE BRUSH SET FOR AUTOMOTIVE AND WORKSHOP

With extension and plastic handle.




Sizes	ø 9 - 11 - 13 - 15 - 17 - 19 mm
Material	Nylon - Steel - Brass

SMC275

HAND BRUSHES

For hand cleaning operations.




Size	275 mm
------	--------

SMC275I

HAND BRUSHES

For hand cleaning operations.



Size	275 mm
------	--------